FENDER MODEL "BANDMASTER-AMP AB763" SCHEMATIC P/B NOTICE

THIS PRODUCT MANUFACTURED UNDER ONE OR MORE OF THE FOLLOWING U.S. PATENTS - #2817708, #2973681, 192859 / PATENTS PENDING

C-FD

1. VOLTAGES READ TO GROUND WITH ELECTRONIC VOLTMETER VALUES SHOWN + OR - 20%.
2. ALL RESISTORS 1/2 WATT, 10% TOLERANCE IF NOT SPECIFIED.
3. ALL CAPACITORS AT LEAST 400 VOLT RATING IF NOT SPECIFIED.

VIBRATO

7025

2 1 68K 68K 1M 25 25 1500 +26V. +1.9V. 100K 250PF 100K TREBLE 250K-A 2-35 BASS 250K-A .047 6800 VOLUME 1M-A 2-35 120PF BRIGHT +27.5V. +2.0V. A 100K 220K + 375V.

820

12AT7

+230V. 500 PF 22K 470 +110V. +108.5V. 1M .1-200 100 82K 5% 100K 5% +225V. .1

6L6GC

+440V. 1500 470 1W 220K 5% 220K 5% 1500 470 1W +440V. -48V. +440V.

TR3

EXT. SPKR.

ON EXPORT MODEL
TR1-125P7DX
TR1-125P7D
TR2-125C1A
TR3-125A6A

VIBRATO PEDAL

12AX7

1M .1 .01 .02 3M-RA SPEED 100K +280V. 1M 2.2M +2.1V. 25 25 2700 220K +380V. +5.4V. 25 25 10M 100K 100K INTENSITY 50K-RA B +440V.

6L6GC

+430V. +375V. D C B TR2 4700 1K 20-525 20-525 20-525

NORMAL

2 1 68K 68K 1M +2.0V. 25 25 1500 +26V. 100K 250PF 100K TREBLE 250K-A 2-35 BASS 250K-A .047 6800 VOLUME 1M-A 2-35 120PF BRIGHT 7025 +26.5V. .047 220K A +2.0V. 820 25 25 100K D +375V.

15K 10K-L 1 25-+50V. 470 1W

STAND BY SWITCH

TR1 320VAC 320VAC 70-350 220K 1W 70-350 220K 1W

.047-600V. AC SWITCH AC RECEPTACLE GROUND SWITCH 2A. SLO. BLO. FUSE TO ALL 6.3 VOLT HEATERS & PILOT LIGHT

FENDER ELECTRIC INSTRUMENT COMPANY
FULLERTON, CALIFORNIA

FENDER MODEL "BANDMASTER-AMP AB763" LAYOUT

P/B **NOTICE** C-FD

VOLTAGES READ TO GROUND WITH ELECTRONIC VOLTMETER VALUES SHOWN + OR - 20%.