



CAUTION 500 VOLTS AVAILABLE. DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 30 SECONDS MINIMUM FOR BLEEDERS TO DISSIPATE 8+ VOLTAGES.

FENDER MUSICAL INSTRUMENTS

CBS MUSICAL INSTRUMENTS
A DIVISION OF CBS INC
FULLERTON CALIFORNIA
U.S.A.

TEST DATA

1V DENOTES TYPICAL 1K Ω SIGNAL FOR 10 WATTS OUTPUT AND 450MV REVERB INPUT UNIT DRIVE
1A INSERT 18A PLUG INTO INPUT JACK FOR THIS TEST.
CONTROL SETTINGS- EQUALIZERS AT MID POSITION.
DISTORTION PRESENCE AT MINIMUM.
OTHERS AT MAXIMUM.

1A-USE 0.1MFD 600V CAPACITOR IN SERIES WITH GENERATOR.
D.C. VOLTAGES READ WITH NO SIGNAL INPUT AND DISTORTION OFF².

1 035604 CONDUCTS WITH DISTORTION ON³.

3. USED IN SOME VERSION.
2. ALL RESISTORS ARE 1/2W, 10%.
1. ALL CAPACITORS AT LEAST 600 V.D.C.

NOTES: UNLESS OTHERWISE SPECIFIED

Fender / Reverb / Rhodes
DESIGNED BY FRED T. SHERMAN
 ENGINEER, ELECTRONIC DIVISION OF CBS INC.

- SCHEMATIC -
 180 WATT
 SUPER TWIN REVERB

013606